

California UltraLite® Pads

Description

Designed specifically for the earthquake-prone regions of the West Coast, The California Ultralite Pad simplifies meeting code requirements for mounting HVAC outdoor equipment. The concrete outer skin and EPS foam inner core provide flexibility and vibration dampening needed to endure extreme vibration. Available in 3", compliant to International Mechanical Code requirements.

Application

- HVAC outdoor units in earthquake-prone regions
- Installation: pad should be placed on compacted level soil, gravel, or harder surfaces, including but not limited to concrete or asphalt, as well as TPO rooftop applications.

Features

- Available in Southern California, select areas of Oregon, and Washington state
- Design is similar to the Ultralight Pad, with the addition of an internal metal band, allowing unit strap attachment
- Lightweight, durable, and optimized for HVAC outdoor unit weights
- Concrete outer skin and EPS foam core provide flexibility and vibration dampening
- Environmentally friendly – made from 15% recycled material
- Non-skid surface
- Unaffected by water, soil, fungus, bacteria, UV exposure or extreme weather
- Concrete gray color
- Drillable for securing unit
 - #8 x ¾ self-tapping sheet metal screws recommended for side metal band
 - ¼ x 1-¼" Tapcon® recommended for top surface

Specifications

- 7000+ PSI reinforced concrete + ASTM Type 1 EPS foam core + internal metal band
- Recommended temperature range: -48°F to 180°F
- Heat/flame resistance:
 - Resists incidental torch contact
 - Not to be used under continuous heating devices, such as water heaters
- Tested per ASTM C67 (flawless performance under 25-cycle testing regimen)
- Tested per ASTM D2299. Does not crack, flake, or warp when subjected to...
 - R-22 or R134a refrigerant
 - Compressor oil
 - Salt solution (20% by volume)
 - Synthetic canine urine

Made in USA by DiversiTech

Warranty

Limited lifetime warranty



General Specification

| Catalog No. | Size | UPC | Quantity per Pallet | Weight per Pad | Weight per Pallet |
|-------------|----------------|---------------|---------------------|----------------|-------------------|
| UC2424-3CA | 3" x 24" x 24" | 0095247105021 | 15 | 14 | 241 |
| UC2436-3CA | 3" x 24" x 36" | 0095247105038 | 15 | 22 | 349 |
| UC2636-3CA | 3" x 26" x 36" | 0095247105045 | 15 | 29 | 428 |
| UC2838-3CA | 3" x 28" x 38" | 0095247105052 | 15 | 26 | 411 |
| UC3030-3CA | 3" x 30" x 30" | 0095247105069 | 15 | 22 | 351 |
| UC3036-3CA | 3" x 30" x 36" | 0095247105076 | 15 | 25 | 400 |
| UC3040-3CA | 3" x 30" x 40" | 0095247105083 | 15 | 34 | 510 |
| UC3232-3CA | 3" x 32" x 32" | 0095247105106 | 15 | 24 | 381 |
| UC3445-3CA | 3" x 34" x 45" | 0095247105120 | 15 | 33 | 516 |
| UC3636-3CA | 3" x 36" x 36" | 0095247095179 | 15 | 28 | 441 |
| UC3642-3CA | 3" x 36" x 42" | 0095247105144 | 15 | 32 | 510 |
| UC3648-3CA | 3" x 36" x 48" | 0095247105151 | 15 | 37 | 579 |
| UC4040-3CA | 3" x 40" x 40" | 0095247105205 | 15 | 34 | 510 |