

WhisperCeiling™ 380 CFM Ceiling Mounted Fan

FV-40VQ3

MORE DETAILS

- o Air Volume (CFM) 380
- (348 at 0.25" static pressure)
- o Noise (sones) 3.0
- Power Consumption (Watts) 112 (111 at 0.25" static pressure)
- Energy Efficiency (CFM's/Watt) 3.4 (3.1 at 0.25" static pressure)
- Speed (RPM) 736 (823 at 0.25" static pressure)
- Current (Amps) 0.94 (0.92 at 0.25" static pressure)
- Power Rating (V/Hz) 120/60
- Motor Type Condenser
- o Type of Motor Bearing Ball
- Thermal Fuse Protection Yes
- o Blower Wheel Type Sirocco
- o Duct Diameter (inches) 6"
- o Mounting Opening (inches sq.) 14 3/4"
- o Grille Size (inches sq.) 17 11/16"
- SmartActionTM Motion Sensor No
- CustomVentTM Variable Speed Control No
- SmartFlowTM Optimum CFM Technology No
- o Light No
- UL Listed for Tub/ Shower Enclosure Yes, when used with a GFCI branch circuit wire
- Washington State VIAQ Code Yes
- o Mfg in ISO 9001 Certified Facility Yes
- Super Quiet Operation Yes

- Energy Star Qualified Yes
- o Totally Enclosed Condenser Motor Yes, for long life Rated for continuous run
- Easy Installation Yes
- o Rust Proof Paint Treatment Yes, on galvanized housing
- o Built-In Damper Yes, to prevent back draft
- Contemporary Grille Design Yes
- Weight 27.3 pounds
- **UPC**092281134512